



Key Features	Benefits
Trailer-Based Winder	Can be towed behind Ute, Quad or Tractor
Storage for Additional Rolls	Able to transport additional rolls of cloth between rows
Low Hydraulic Flow Rate	Can be operated off the tractor hydraulics or independent power-pack
Adjustable Ground Anchors	<ul> <li>Grounds the trailer from pulling sideways</li> <li>Used to adjust the trailer angle to track the cloth during winding</li> </ul>





4-Metre Cloth Width	Able to wind all cloth widths up to 4m wide
Trailer Light-Pack for Road Use	<ul> <li>Option of trailer light-pack and mud guards for legal towing on the road</li> <li>Able to be towed between orchard blocks behind a Ute or Tractor</li> </ul>
Safety Features	<ul> <li>Maximum winding pressure can be adjusted to minimise cloth damage and increase operator safety</li> <li>Hydraulic control lever returns to off-position when released</li> <li>Optional hydraulic foot-control available for additional operator safety</li> <li>Optional E-stops available for either end of the winder for additional operator safety</li> </ul>
Mud-Guards for Road Use	<ul> <li>Full-coverage mud guards for road use and to eliminate mud splashing onto the ground-sheet during transport</li> </ul>

## **GROUNDwinder Specifications**

Length: 6000mm

Width: 1500mm (transport mode)
Width: 2000mm (operation mode)

Hydraulic Flow Rate: 25 L/min (single remote)

Hydraulic Pressure Adjustment : 0 to 180 Bar (full range adjustment)

E-Stops : Up to 2 E-Stops (optional feature)

Trailer Lights: LED Tail-lights, brake-lights and indication-lights (optional)

Wheel Mud-Guards: Full mud-guards for road use

